



Yeastar S-Series VoIP PBX

Performance and Power

Designed with the small and medium sized enterprises in mind, supporting up to 500 users and built using the very latest technology, the Yeastar S-Series delivers exceptional cost savings, productivity and efficiency improvements, delivering power, performance, quality and peace of mind.

The all new S-Series is engineered for the communications needs of today and tomorrow, and with the Yeastar unique modular design future proofs your investment choice.

Appreciate the Easy-to-use Solution

The S-Series features fast installation with comprehensive auto provisioning, advanced plug and play capability, together with an intuitive Metro UI driven by point-and-click configuration, from any location.

Your Choice of Technologies and Features

With a unique modular design, the S-Series will install into the most demanding of environments. You can also take advantage of advanced enterprise grade features with the fullest and most complete software versions.

Telephone System without Risk

S-Series is built with the future in mind, utilizing the latest technology advances, from Freescale industrial grade Quad Core processors, TI DSP voice processors, and long-life power units and lightning protection.

Play Safe and Expect Reliability

With advanced failover, security, monitoring and reporting capabilities as standard, combined with an internal firewall and with support for TLS and SRTP encryption, there has never been such a robust system.

Key Features and Benefits

- Works with SIP/IAX2, PSTN lines, ISDN BRI, E1/T1/PRI, and GSM/CDMA/3G
- Built-in call recording capability
- Powerful Apps (add-ons) include Auto Provision, LDAP, and more coming soon
- Free lifetime software/firmware upgrade and above all, it's super easy
- Connect multiple sites and remote users instantly
- No hidden charges and extra licensing fees
- Low power consumption (1.8-59.1 watt)

FEATURES

- Automated Attendant (IVR)
- Custom Prompt
- One Touch Recording
- Attended Transfer
- Dial by Name
- Queue
- AutoCLIP
- DISA
- PIN List
- Blind Transfer
- Distinctive Ringtone
- Phone Provisioning
- Blacklist/Whitelist
- DNIS
- Real-time Status Monitor
- Call Back
- Do Not Disturb (DND)
- Ring Group
- Call Detail Records (CDR)
- Event Center
- SIP Forking
- Call Forwarding
- Email to SMS/SMS to Email
- Skype Integration
- Call Monitor
- Fax to Email
- Speed Dial
- Call Parking
- Follow Me
- Time Condition
- Call Pickup
- Paging/Intercom
- User Portal
- Call Recording
- LDAP
- User Permission
- Call Routing
- Mobility Extension
- Video Calls
- Call Waiting
- Multi-language System Prompt
- Voicemail
- Caller ID
- Multi-language Web GUI
- Voicemail to Email
- Conference
- Music on Hold
- Voicemail Forwarding

SPECIFICATIONS

	S20	S50	S100	S300
Users	20	50	100 (up to 200)	300 (up to 500)
Max Concurrent Calls	10	25	30 (up to 60)	60 (up to 120)*
Max Analog Ports	4	8	16	24
Max BRI Ports	4	8	16	24
Max Cellular Ports	1	4	6	6
Max E1/T1/J1 Ports	–	–	2	3
VoIP Trunks	20	50	100	100
Protocol	SIP (RFC3261), IAX2			
Transport Protocol	UDP, TCP, TLS, SRTP			
Codec	G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC, H263, H263P, H264, MPEG4			
DTMF	In-band, RFC4733, RFC2833, SIP INFO			
LAN	1 × 10/100 Mbps	1 × 10/100/1000 Mbps		
WAN	1 × 10/100 Mbps	1 × 10/100/1000 Mbps		
IP Services	Static IP, DHCP, VPN, Firewall, VLAN, DDNS, PPPoE, QoS, Static NAT, STUN			
Voicemail	5000 min (expandable)		10000 min (expandable)	
Firewall	Yes	Yes	Yes	Yes
T.38 Fax	Yes	Yes	Yes	Yes
App Center	Yes	Yes	Yes	Yes
External Storage	TF Card	SD Card	SD Card	SD Card & 2.5 inch SATA HDD
USB	–	–	1	1
Power	DC 12V 1A	AC 100-240V 50/60HZ 0.6A max	AC 100-240V 50/60HZ 1.8A max	
Size (L x W x H) (cm)	16 x 16 x 3	34 x 21 x 4.4	44 x 25.2 x 4.4	44 x 25.2 x 4.4
Weight	0.3 kg	1.48 kg	2.5 kg	2.6 kg
Power Consumption	1.8-10.6 W	2.1-18.5 W	5.5-41.2 W	6.2-59.1 W
Environment	Operation Range: 0°C to 40°C, 32°F to 104°F; Storage Range: -20°C to 65°C, -4°F to 149°F; Humidity: 10-90% non-condensing			
Mounting	Desktop & Wall-mount		1U Rack-mount	

*If automatic call recording is enabled, the max concurrent calls will be 90.