



MTG600 Enterprise Trunk Gateway

MTG600 is a trunk gateway aimed at small and medium enterprise, and used to help enterprise to realize the evolution from the traditional PBX to voice IP. On the one hand, it supports PRI/SS7 protocol and adopts standard T1/E1 trunk interface to realize docking with traditional PBX. On the other hand, it adopts standard SIP protocol docking with various soft switch to ensure PSTN seamless access to IP voice/NGN network, and achieves VoIP/FoIP and more value-added service. MTG600 supports intelligent multiple trunk routing technology, makes the operator easy to manage trunk routing by price optimum rule, and the automatic switch-over between multiple trunk routing makes the network have high reliability.

Product Pictures



Key Benefits

- The strong performance of hardware platform, energy efficiency concurrent processing
- Service oriented architecture, rich services, in addition to support voice and IP fax outside, still can be expanded to fax server
- Flexible dial-up rules and operation, in order to adapt to the different work scene.
- Voice codec: G.711A/U,G.723.1,G.729A/B, iLBC
- Good compatibility, support Asterisk, Elastix, Freeswitch and Small and medium IPPBX

Decade Focused

Creates the High-quality Products

Voice & Fax

- G.711A/U law, G.723.1, G.729A/B, iLBC
- Silence Suppression & Detection
- Comfort Noise Generation (CNG)
- Voice Activity Detection (VAD)
- Echo Cancellation (G.168)
- Adaptive (Dynamic) Jitter Buffer
- Call Progress Tone Generation
- Programmable Gain Control
- T.38/Pass-through fax, up to 14.4kbps
- Modem
- RFC3407
- FAX/X-FAX
- QoS control: ToS, DS

Call Feature

- DTMF:RFC2833, SIP INFO, INBAND
- Back tone/busy tone control
- Digit Map
- Dial rule configuration, max 2000 rules
- Overlap receiving
- Dial time control
- Time slot group management
- E1/T1 port group management

Protocol & IP Feature

- SIP-RFC 3261, 3262,3263,3264, 3265,3515,2976,3311
- SDP -RFC 2327
- RTP/RTCP-RFC2198,1889
- SIP-T,RFC3372, RFC3204, RFC3398
- SIP domain register
- IP group management
- Trunk priority management
- Peer/Access work mode
- IP address/domain authentication
- SIP username/password register to remote

Signal

- PRI/PRA
ISDN E1/T1
ITU-T I.431, Q.921, Q.931, ETSI Q.sig
- SS7/No.7
ITU, ANSI, ETSI, ITU-China,
MTP layer 1/2/3, ISUP/TUP
- R2
Support China, Vietnam etc 23 country
standard
- SS7 MTP link management
- SS7 circuit maintenance



Customer First Services More Intimately

Maintain & Upgrade

- Web based configuration
- HTTP/Telnet configuration
- Data backup/restore
- Support English and China language
- Firmware upgrade by TFTP
- Web & telnet login password modify
- SNMP management
- Syslog: Debug, Info, Error, Warning, Notice
- CDR
- NTP Configuration

Physical Properties

- Power supply: 110~220VAC,50-60Hz
- Power consumption: 10w
- Temperature(operation): 0 °C ~ 45 °C
(storage): -20 °C ~80 °C
- Operation Humidity: 10%-90% no condensation
- Dimension(w/D/H): 300*200*44mm
- Weight: 1.29kg
- Color & material: black, iron box

Routing & Num manipulation

- Routing rules
PSTN-PSTN, PSTN-IP, IP-IP, IP-PSTN
- Intelligent routing
- Routing time control
- 256 routing rules
- Caller/callee manipulation
- 128 number manipulation

Physical Interface

- Interfaces: 1/2/4*E1/T1, G.703, 120Ω RJ-48
- Ethernet Interface:
FE0(WAN):service eth interface),
FE1(LAN):management eth interface)
*10/100M Base-Tx RJ45
- Management Interface:
1 Console 115200bps

Network Protocol

- IP,TCP, UDP,TFTP, FTP, RTP, RTCP, ARP/RARP,ICMP Ping, NTP, SNTP, HTTP, DNS

Certifications

- CE,
FCC